# ISC2-200

Second Generation Smart Booster Pump

The ISC2-200 is the second generation of the ISC DC booster, and its difference is on the panel: two-button control replaces single-button operation, so each action takes one fingertip press. Under the panel it keeps the same core — 200 W on DC 24 V, 25 L/min, 25 m of head, a 1 kg body, IP65 protection and 15 mm ports — with an adapter for AC 110 V / 220 V input. It is the simplest DC booster to operate, with the 1-year DC warranty. **Energy:** The second-generation DC drive uses only the power the duty calls for, instead of running flat out like a conventional fixed-speed pump.

## Key features

- Two button control for stop and mode change on the unit
- Power, flow and auto indicator lights on the front panel
- Automatic start and stop with constant pressure output
- Permanent magnet DC motor on a 24 V supply, IP65 housing
- Curve falls from 25 m at shut off to about 0 m at 25 L/min
- 15 mm threaded inlet and outlet, 1 kg body

## Technical data

| | |
|---|---|
| **Control** | 2 Buttons |
| **Temperature** | 0 - 65 °C |
| **Connection** | 15 mm |
| **Insulation class** | Class H |
| **Protection** | IP65 |
| **Color** | White / Black |
| **Power** | 200 W |
| **Voltage** | DC 24 V |
| **Max head** | 25 m |
| **Max flow** | 25 L/min |
| **Pump body** | Reinforced Nylon |
| **Weight** | 1 kg |
| **Size** | 5.5 x 8 x 13 cm |

## Working conditions

| | |
|---|---|
| **Temperature** | 0 - 65 °C |
| **Protection** | IP65 |
| **Media** | Clean water |
| **Mounting** | Inlet and outlet threaded 15 mm |

## Installation


The specification confirmed for an order is the one stated in the order confirmation.

| Model | Inlet | Outlet | Net weight |
|---|---|---|---|
| ISC2-200 | 15 mm | 15 mm | 1 kg |

## Packing

| | |
|---|---|
| **Packing** | Carton |
| **Net weight** | 1 kg |

## Applications

- Pipeline Boosting
- Hot Water Areas
- Tap & Fixture Boosting
- RV & Caravan Water Supply

---

Fujian Calliope Pumps Co., Ltd. — For quotations, OEM/ODM projects and distributor applications, contact the export team at cason@calliopepump.com or via WhatsApp +86 178 0591 6566. See the full model page at www.calliopepump.com/products/isc2-200.


The specification confirmed for an order is the one stated in the order confirmation.